

CUSTOMER FOCUSED. SOLUTION DRIVEN.



PP-25 Power Pack

- 49.5 HP Kubota Diesel Engine, Tier 4 Final
 - 25 gal per minute at 2250 psi
- Adjustable hydraulic pressure and flow control
 - Lifting harness included

STANDARD FEATURES

Frame

- Skid mounted steel frame, partially encased
- Forklift slots
- Powder coat
- Lifting harness included

Operating Elements

- Manual adjustable flow control
- Manual adjustable hydraulic pressure

Diesel Drive

- Four-cylinder Kubota Diesel Engine, Tier 4 Final, liquid-cooled
- 49.5 HP
- Tank capacity approximately 95 l (25 U.S. gal)
- Starter battery
- Fuel Burn Rate:
 - 2200 rpm = 2.22 gal/h
 - 2400 rpm = 2.48 gal/h

Hydraulic

- Oil tank capacity approximately 151 l (40 U.S. gal)
- Oil level and temperature indication
- Electric cooling fan
- Quick couplers on the hydraulic connection

Specifications

- Dimensions: 48W x 48L x 48H
- Weight: 2000 lbs

NOW DELIVERING TO U.S. MARKETS.

Contact Ben VanderWeide at 855.801.7453.

INTRIC
GROUTING SOLUTIONS

www.INTRICSOLUTIONS.com