

CUSTOMER FOCUSED. SOLUTION DRIVEN.



# DT650 Mixing Station



## STANDARD FEATURES

### Frame

- Containerized steel frame
- Forklift slots
- Lifting hooks
- Powder coat

### Water Dosage

- Water distributor with optional flushing connection
- Two water-holding and dosing tanks, V=560 l (150 U.S. gal) each
- Hydraulic operated discharge valve

### Operating Elements

- Fully automatic water dosage
- Fully automatic mixing capabilities with pre-adjusted recipe
- Mixing tanks on load cells for automatic mixing control
- Digital screen for data logging and recipe input

### Mixing Tanks

- Round stainless steel tanks, bottom inclined to outlet
- Two tanks, capacity 650 l (170 U.S. gal) each
- Hopper with two silo connections for solids
- High-shear mixing tool mounted on the middle on mixing shaft, high-shear mixing and colloidal tool mounted on mixing shaft bottom part
- Mixing speed 1800 rpm hydraulic driven
- Mixing performance on W/C ratio down to 0.45 by weight
- Drive bearing above the mixing level
- No packing seal, therefore runs dry without problems
- Mixing tanks act as storage tanks and/or can transfer to external storage tank

### Hydraulic

- Two oil tanks, capacity approximately 170 l (45 U.S. gal) each
- Oil level and temperature indication
- Two electric cooling fans

### Electric Drives

- Two 30 HP electric motors

### Additional Features

- Integrated pressure washer
- Six work lights

### Specifications

- Dimensions: 75"W x 180"L x 96"H
- Weight: 8200 lbs

**NOW DELIVERING TO U.S. MARKETS.**

Contact Ben VanderWeide at 855.801.7453.

**INTRIC**  
GROUTING SOLUTIONS

[www.INTRICSOLUTIONS.com](http://www.INTRICSOLUTIONS.com)